

If your telephone system does not contain an inexo profile, please use the following settings:

SIP-Settings (Class 5; User-/Password-Authenticated)

Username: Phone number in an international format (area code without 0 but with 49)
point-to- multipoint: e.g. 06831-4711 = 4968314711,
point-to-point: e.g. 06831-4711-0 = 49683147110
Registrar/Domain: business.voip.inexo.net

Port: 5060 Transport-Protocol: UDP

STUN-Server: not required

NAT: may be used

Encryption: none

Supported Standards:

CLIPNoScreening:	possible (via P-Preferred-Identity)
CFU (Call Forwarding Unconditional):	yes
CFNR (Call Forwarding on No Reply):	yes
CFB (Call Forwarding Busy):	yes
CLIP/CLIR:	yes
DDI:	yes
Partial Rerouting/Call Deflection:	yes
Advice of Charge:	AOC-D
DTMF:	Inband, RFC 2833, SIP INFO (recommended Inband and RFC 2833)
Faxes:	no support of G4
Supported Codecs:	G.711a, G722, CLEARMODE, T.38

Further information:

The **FROM-Header** must contain the username (see above).

The displayed number must be in the **P- Preferred-Identity Header** as it is to be displayed to the caller (e.g. 06831471110).

The **UDP NAT timeout of the firewall** must be greater than 60 seconds. T

The **Packetization Time** (ptime) should be 20ms.

Enable in firewall:

IPv4:

SIP: 37.157.47.128/28; 128.0.99.128/28

RTP: 37.157.47.144/28; 128.0.99.144/28

IPv6:

SIP: 2a01:05c0:0006:0007::/64; 2a01:05c0:0006:0032::/64

RTP: 2a01:05c0:0006:0031::/64; 2a01:05c0:0006:0033::/64